

# ALL EASY PRO

## Quattro Full DC Inverter



**Compact body, better efficiency, less work!**

	ECO MODE		LOUVER MEMORY		SUPER IONIZER		EMERGENCY OPERATION
	1W STANDBY		FOLLOW ME		HIGH DENSITY FILTER		EASY MAINTENANCE
	HORIZONTAL SWING		DEHUMIDIFICATION FUNCTION		BACTERIAL+DUST REMOVAL		TWO-WAY DRAINING
	VERTICAL SWING		SELF CLEANING		COLD CATALYST FILTER		24H TIMER
	QUIET MODE		REFRIGERANT LEAKAGE DETECT		FROST PROTECTION		WIFI CONTROL
	NIGHT MODE		SELF DIAGNOSIS		GEAR CHANGE		OPTIONAL WIRED CONTROL
	TURBO MODE		AUTO RESTART		INTELLIGENT EYE		DIAMOND EDGED CASINGS



# ALL EASY PRO

## Quattro Full DC Inverter



- The louvers of the indoor unit of the air conditioner move automatically in all directions.
- Easy Installation and Maintenance.
- Ultra-low noise level.
- Adaptive in extreme climatic conditions.
- Innovative *Intelligent Eye* function, reducing the energy cost by 25%.
- Possibility to set the operating power of the compressor to 50%, 75% or 100%.
- With Auto restart function.
- High Density filter and *Super Ionizer* technology ensures a clean atmosphere free of dust, odors, and microorganisms.
- Seasonal SEER to A+++ and SCOP A+++ performance ratings.
- Via Wi-Fi you control your unit wherever you are.

Direct control of your air conditioner wherever and whenever you are via your smartphone with the Midea Air app.



ALL EASY PRO		TECHNICAL SPECIFICATIONS							
MODEL		9,000 BTU		12,000 BTU		18,000 BTU		24,000 BTU	
CODE	Indoor	MSEPBU-09HRFN8		MSEPBU-12HRFN8		MSEPCU-18HRFN8		MSEPDU-24HRFN8	
	Outdoor	MOX330-09HFN8		MOX330-12HFN8		MOX430-18HFN8		MOX430-24HFN8	
FUNCTION		COOLING	HEATING	COOLING	HEATING	COOLING	HEATING	COOLING	HEATING
Capacity*	W	2720	3130	3520	3960	5270	5570	7030	7330
	Btu/h	9300	10700	12000	13500	18000	19000	24000	25000
Capacity Range*	W	1320 - 3810	880 - 4400	1320 - 3960	880 - 4540	3750 - 6120	2580 - 6770	2110 - 8200	1550 - 820
	Btu/h	4500 - 13000	3000 - 15000	4500 - 13500	3000 - 15500	6800 - 20900	4600 - 23100	7200 - 28000	5300 - 28000
Power Input (min-nom-max)	W	600	690	880	990	1318	1500	1760	1975
Current Input (nom)	A	2.66	3.05	3.9	4.4	5.73	6.52	7.7	8.6
SEER*	-	8.6	-	8.5	-	8.5	-	8.5	-
SCOP*	-	-	5.1	-	5.1	-	5.4	-	5.3
Energy efficiency class*	-	A+++	A+++	A+++	A+++	A+++	A+++	A+++	A+++
Operation Range	°C	-15~50	-20~24	-15~50	-20~24	-15~50	-20~24	-15~50	-20~24
Power Supply	V/Ph/Hz	220-240 / 1 / 50		220-240 / 1 / 50		220-240 / 1 / 50		220-240 / 1 / 50	
Electric Fuse	A	16		16		16		16	
Air Flow Volume	m³/h	530/360/280		560/380/290		685/580/400		1092/724/379	
Application Area	m²	12 - 18		16 - 23		24 - 35		32 - 47	
Sound Pressure Level	Indoor	37/32/21.5/20.5		40/33/22/21		41/35/23/22		44.5/40/33/21	
	Outdoor	57		57.5		56		58.5	
Sound Power Level	Indoor	58		59		59		64	
	Outdoor	64		65		65		67	
Refrigerant	-	R32		R32		R32		R32	
Liquid - gas pipe diameter	Inch	1/4" - 3/8"		1/4" - 3/8"		1/4" - 1/2"		3/8" - 5/8"	
Maximum pipe length	m	25		25		30		30	
Maximum pipe height	m	10		10		20		20	
Unit dimensions WxHxB	Indoor	795x295x225		795x295x225		965x319x239		1140x370x275	
	Outdoor	805x554x330		805x554x330		890x673x342		890x673x342	
Weight	Indoor	10.2		10.2		12.3		44.5	
	Outdoor	28.4		28.4		38.8		58.5	

\*Warm climate zone